

## TECHNICAL INFORMATIONS

# UNA BRANCO

## 15W 4000K

Downlight com temperatura de luz de 4000K, design elegante, lente opal para um desempenho superior e alta proteção (IP54).

Versatile Dimmable Downlight with color temperature 4000K, stylish design, opal lens for superior performance and high protection (IP54).

Downlight con temperatura de la luz 4000K, diseño elegante, lente opal para un rendimiento superior y alta protección (IP54).




### ILAR-01001


| REFERENCE                          |               | DIMENSION & WEIGHT |              | PHOTOMETRICAL DATA     |         |
|------------------------------------|---------------|--------------------|--------------|------------------------|---------|
| Reference                          | ILAR-01001    | Lenght             | Ø145mm       | Total Luminous Flux    | 1560lm  |
| LED Brand                          | Sanan         | Width              | -            | Luminous Efficacy      | 105lm/w |
| Mounting Type                      | Recessed      | Height             | 45mm         | Beam Angle             | 90°     |
| Body Material                      | Aluminium     | Weight             | 0.81         | Colour Temperature     | 4000K   |
| Housing Colour                     | White RAL9016 | Cutout             | Ø120-130mm   | Colour Rendering Index | >80     |
| Body Shape                         | Round         | Packaging Unit     | 10pcs/carton | Colour Consistency     | <=6     |
| Nominal Lifetime (EOL end of life) | 50.000H       | Gross Weight       | 10.5kg       | UGR                    | -       |
| Dimmable                           | YES           |                    |              |                        |         |

| ELECTRICAL AND OPERATING DATA |                | ENERGY LABEL & STANDARS                |          | CERTIFICATIONS             |         |
|-------------------------------|----------------|--|----------|----------------------------|---------|
| Nominal Wattage               | 15W            | Energy Label                           | -        | 2014/30/EU (EMC Directive) | YES     |
| Nominal Voltage               | 200-240V       | Energy Consumption KWH/1000H           | -        | 2014/35/EU (LVD Directive) | YES     |
| Operating Frequency           | 50Hz           | Type of Protection                     | IP54     | ROHS                       | YES     |
| Power Factor                  | ≥0.9           | Protection Class                       | Class II | ENEC                       | -       |
| Operating Temperature         | -20°C to +45°C | Proteccion Class IK (shock resistance) | -        | Warranty                   | 3 YEARS |
| Starting Time 100% ON         | 0.0001s        |  |          |                            |         |
| ON/OFF Cycles                 | 100.000        |  |          |                            |         |

### SIZE



### BEAM ANGLE



Designed by Aron Light in Portugal. Made in PRC

