

## TECHNICAL INFORMATIONS

### PRADO ECO

### 30W 4000K

Projektor de calha orientável com tecnologia de alumínio em fundição injetada. Performance técnica de elevada reprodução cromática.

Orientable Track Light with die-cast aluminum technology, high geometric accuracy and high-precision surface finish. The High color rendering index.

Proyector de carril orientable con tecnología de aluminio en fundición inyectada. El rendimiento técnico de alta reproducción cromática.




#### ILAR-01234


REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-01234	Length	-	Total Luminous Flux	2400lm
Led Brand	Bridgelux	Width	Ø82mm	Luminous Efficacy	80lm/w
Mounting Type	Track Light	Height	155mm	Beam Angle	24°
Body Material	Aluminium	Weight	-	Colour Temperature	4000K
Housing Colour	White	Cutout	-	Colour Rendering Index	>90
Driver Brand	Lifud Driver	Packaging Unit	Carton box 10 pcs	Colour Consistency	<=4
Nominal Lifetime (EOL end of life)	50.000h	Gross Weight	11.2Kg	UGR	<19
Dimmable	No	Volume	-		

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	30W	Energy Label	A+	2014/30/EU (EMC Directive)	YES
Nominal Voltage	200-240V	Energy Consumption KWH/1000H	30kWh	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Type of Protection	IP20	ROHS	YES
Power Factor	0.9	Protection Class	Class II	Warranty	3 YEARS
Operating Temperature	- 30°C to + 40°C	Proteccion Class IK (shock resistance)	IK03		
Starting Time 100% ON	0.0001 s				
ON/OFF Cycles	>15000				

#### SIZE



#### BEAM ANGLE



Designed by Aron Light in Portugal. Made in PRC

