

TECHNICAL INFORMATIONS

INTEL TRI-PROOF 150LM/W

43W 4000K 150CM

Luminária com elevada proteção IP66 e IK10. Possui uma eficiência de 150Lm/W e tempo de vida de 50.000H (5 anos garantia). Possibilidade de instalação saliente ou suspensa.

Luminaire with high protection IP66 and IK10. It has an efficiency of 150Lm / W and a lifetime of 50,000H (5 year warranty). Possibility of installation outgoing or suspended.

Luminaria con alta proteccion IP66 e IK10. Tiene una eficiencia de 150Lm / W y un tiempo de vida de 50.000H (5 años de garantía). Posibilidad de instalación saliente o suspendida.



ILAR-02441

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Body Material	PC+Aluminum inside	Dimensions	1500x66.5x70.5mm	Total Luminous Flux	6450lm
Diffuser Material	PC	Net Weight	1.1kg	Luminous Efficacy	150lm/W
Housing Colour	White	Packaging Unit	Carton Box 12 pcs	Beam Angle	120°
Nominal Lifetime (EOL end of life)	50.000hrs	Gross Weight	17kg	Colour Temperature	4000K
Dimmable	DALI / 1-10V (Optional)	Volume	0.09cbm	Colour Rendering Index	≥83
Emergency	Optional (3H)			UGR	<21

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	43W	Type of Protection	IP66	2014/30/EU (EMC Directive)	YES
Nominal Voltage	220-240V	Protection Class	Class II	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Protection Class IK (shock resistance)	IK10	ROHS	YES
Operating Temperature	- 20° C to + 40° C			CE	YES
				ENEC	YES
				Warranty	5 YEARS

SIZE	BEAM ANGLE	ACCESSORIES
		<p>ILAR-02445 Microwave Sensor for TRI-PROOF</p> <p>ILAR-02446 PIR Sensor for TRI-PROOF</p> <p>ILAR-02447 Emergency Kit for TRI-PROOF</p>

Designed by Aron Light in Portugal. Made in PRC

