



## TECHNICAL INFORMATIONS

# ATEX LINEARTOP


## 40W 1.2M 5000K



### ILAR-02852

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Body Material	Aluminum alloy (ADC12)	Dimensions	1200x125x100mm	Total Luminous Flux	4800lm
Backup battery	Li-ion battery, 12W power			Luminous Efficacy	120lm/W
				Beam Angle	120°
				Colour Temperature	5000K

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	40W	IP Protection	IP66	2014/30/EU (EMC Directive)	YES
Nominal Voltage	100-277V	Protection Class IK (shock resistance)	IK10	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz			ROHS	YES
Operating Temperature	- 10° C to + 45° C			CE	YES
Power Factor	>0.97			Warranty	5 YEARS



SIZE	ATEX RATED LIFTING AND HANDLING EQUIPMENT		
	<p>ATEX HAZARDOUS GAS ENVIRONMENTS: ZONE 1</p>	<p>ATEX HAZARDOUS DUST ENVIRONMENTS: ZONE 21</p>	<p>ATEX HAZARDOUS DUST ENVIRONMENTS: ZONE 22</p>

Designed by Aronlight in Portugal. Made in PRC

