

## TECHNICAL INFORMATION

### FITA LED IP65

### 19.2W 4000K

Linha de Fitas LED de 24V com um índice de reprodução cromática de 94, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a color rendering index of 94, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática de 94, ideal para lugares de exposición donde la calidad del color es un requisito determinante.



#### ILAR-00630

##### REFERENCE

Reference	ILAR-00630
Type	LED ProStrip
Type LED	SMD 2835
Nominal Lifetime (EOL end of life)	30000h

##### DIMENSION & WEIGHT

Length	5000mm
Width	10mm

##### PHOTOMETRICAL DATA

Total Luminous Flux	-
Luminous Efficacy	1152lm/mt
LED/MT	60
Beam Angle	120°
Colour Temperature	4000K
Colour Rendering Index	94

##### ELECTRICAL AND OPERATING DATA

Power Rated	19.2W
Equivalent Wattage	-
Lamp Current	-
Voltage	24V
Nominal Voltage	-
Operating Frequency	-
Power Factor	>0.95
Starting Time	-
Warm - Up Time (60%)	-
Operating Temperature	-20°C to +40°C


##### ENERGY LABEL & STANDARS

Energy Label	A+
Type of Protection	IP65

##### CERTIFICATIONS

CE	YES
ROHS	YES
WARRANTY	2 YEARS

##### SIZE



Designed by Aronlight in Portugal. Made in PRC

