

TECHNICAL INFORMATIONS

HARPE ONE

6W 3000K CINZENTO

Luminária LED para aplicação em fachadas com design moderno, chips LED de elevada reprodução, alumínio de fundição injetada, elevados níveis de proteção (IP65 e IK06) e forte resistência à corrosão.

Facade LED luminaire with modern design, high reproduction LED chips, die-cast aluminum, high levels of protection (IP65 and IK06) and strong corrosion resistance.

Luminaria LED de fachada de diseño moderno, chips LED de alta reproducción, aluminio fundido a presión, altos niveles de protección (IP65 e IK06) y gran resistencia a la corrosión.




ILAR-00961


REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00961	Lenght	100mm	Total Luminous Flux	450lm
LED Type	LED CREE	Width	Ø65mm	Luminous Efficacy	150lm/W
Body Material	Aluminium body in powder coated	Height	95mm	Beam Angle	16°
Housing Colour	Grey	Packaging Unit	Carton Box 20 pcs	Colour Temperature	3000K
Nominal Lifetime (EOL end of life)	30000H	Gross Weight	-	Colour Rendering Index	>80
Surface / Recessed	Surface	Volume	-		
Dimmable	NO				
Installation	Wall				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	6W	Energy Label	A+	2014/30/EU (EMC Directive)	YES
Nominal Voltage	220-240V	Energy Consumption KWH/1000H	6 kWh	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Type of Protection	IP65	ROHS	YES
Operating Temperature	- 20° C to + 50° C	Protection Class	Class I	ENEC	NO
Starting Time 100% ON	0.000s	Proteccion Class IK (shock resistance)	IK06	Warranty	3 YEARS
ON/OFF Cycles	>15000				

SIZE



BEAM ANGLE



Designed by Aron Light in Portugal. Made in PRC

