

TECHNICAL INFORMATION

VALL II

3W 3000K CORTEN

Design moderno, chips LED de elevada reprodução, alumínio de fundição injetada, elevados níveis de proteção (IP e IK), forte resistência à corrosão.

Modern design, high-performance LED chips, injected cast aluminum, high protection levels (IP and IK), strong corrosion resistance.

Diseño moderno, chips LED de alto rendimiento, aluminio fundido inyectado, altos niveles de protección (IP e IK), fuerte resistencia a la corrosión.



ILAR-03733

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-03733	Length	66mm	Total Luminous Flux	190lm
Base	High Purity Aluminium	Width	Ø33mm	Luminous Efficacy	63lm/W
Housing Colour	Corten			Colour Temperature	3000K
Nominal Lifetime (EOL end of life)	25000H			Beam Angle	15°
Driver	Built-in high voltage constant current driver with transformer			CRI	>80

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	3W	Energy Consumption KWH/1000H	15kwh	CE	YES
Nominal Voltage	AC100-245V	Type of Protection	IP67	RoHS	YES
Operating Frequency	50/60Hz	Protection Class	Class I	Warranty	3 YEARS
Operating Temperature	- 25° C to + 45° C	Protection Class IK (shock resistance)	IK04		
Starting Time 100% ON	<0.5s				
ON/OFF Cycles	>20000				

SIZE



Designed by Aronlight in Portugal. Made in PRC

