

TECHNICAL INFORMATIONS

PAINEL ENCASTRAR QUADRADO

9W 6500K BRANCO

Panel de Encastrar e Superfície, ideal para tectos falsos com altura limitada.

Recessed and Surface Panel, ideal for dropped ceiling with limited height.

Panel de Encastrar y Superfície, ideal para techos falsos con altura limitada.

ILAR-01225



REFERENCE

Led Type	SMD
Mounting Type	Recessed
Body Material	Aluminium
Housing Colour	White
Body Shape	Square
LGP	PS
Nominal Lifetime (EOL end of life)	25000hrs
LED Brand	Samsung LED
Useful Lifetime Based on LM70	-
Dimmable	No

DIMENSION & WEIGHT

Lenght	150mm
Width	150mm
Height	20mm
Weight	0.16kg
Cut-Out	135x135mm

PHOTOMETRICAL DATA

Total Luminous Flux	720lm
Luminous Efficacy	83lm/w
Beam Angle	120°
Colour Temperature	6500K
Colour Rendering Index	>80
Colour Consistency	<= 6

ELECTRICAL AND OPERATING DATA

Nominal Wattage	9W
Nominal Voltage	85-265V
Operating Frequency	50/60Hz
Power Factor	0.5
Operating Temperature	- 20° C to + 40° C


ENERGY LABEL & STANDARS

Energy Label	A+
Energy Consumption KWH/1000H	9kwh
Type of Protection	IP44
Protection Class	II
Protection Class IK (shock resistance)	-

CERTIFICATIONS

2014/30/EU (EMC Directive)	YES
2014/35/EU (LVD Directive)	YES
ROHS	YES
Warranty	2 YEARS

SIZE



Designed by Aron Light in Portugal. Made in PRC

