

TECHNICAL INFORMATIONS

SQUARE SURFACE PANEL

24W CCT WHITE

Panel de Encastrar e Superfície, ideal para tectos falsos com altura limitada.

Recessed and Surface Panel, ideal for dropped ceiling with limited height.

Panel de Encastrar y Superficie, ideal para techos falsos con altura limitada.

ILAR-02030



REFERENCE

Led Type	SMD
Mounting Type	Surface
Body Material	Aluminium
Housing Colour	White
Body Shape	Square
LGP	PS
Nominal Lifetime (EOL end of life)	35000hrs
LED Brand	Samsung LED
Dimmable	No

DIMENSION & WEIGHT

Width	300x300mm
Height	35mm
Weight	0.995kg

PHOTOMETRICAL DATA

Total Luminous Flux	2160lm
Luminous Efficacy	90lm/w
Beam Angle	120°
Colour Temperature	6500K
Colour Rendering Index	>80
Colour Consistency	<= 6

ELECTRICAL AND OPERATING DATA

Nominal Wattage	24W
Nominal Voltage	176-264V
Operating Frequency	50/60Hz
Power Factor	0.7
Operating Temperature	- 20° C to + 40° C


ENERGY LABEL & STANDARS

Energy Label	A+
Energy Consumption KWH/1000H	24kwh
Type of Protection	IP44
Protection Class	Class II
Protection Class IK (shock resistance)	IK03

CERTIFICATIONS

2014/30/EU (EMC Directive)	YES
2014/35/EU (LVD Directive)	YES
ROHS	YES
Warranty	2 YEARS

SIZE



Designed by Aron Light in Portugal. Made in PRC

