



TECHNICAL INFORMATIONS

SPECTRA PROJECTOR LED WITH SENSOR


20W 4000K WHITE



ILAR-02893

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-02893	Size Piece	93.8x69.8mm	Total Luminous Flux	1600lm
Led Type	SMD2835			Luminous Efficacy	80Lm/W
Body Material	Die Cast Aluminium			Beam Angle	120°
Body Colour	White RAL 9016			Colour Temperature	4000K
Nominal Lifetime	30000h			Colour Rendering Index	>80
Dimmable	No				
Cable Size	50cm				
ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	20W	Energy Consumption KWH/1000H	6KWH	CE Directive	YES
Nominal Voltage	AC220-240V	Type of Protection	IP65	ROHS	YES
ON/OFF Cycles	>15000	Protection Class	Class I	Warranty	3 YEARS
Operating Frequency	50/60Hz	Protecion Class IK (shock resistance)	IK06		
Power Factor	>0.7				
Operating Temperature	- 30° C to + 40° C				
Power Supply	DOB				
SPD	1KV-2KV				

SIZE



SENSOR DATA

Range	4±2 m
Time (On)	10±5 sec
Lux Level (On)	<10 lux

Designed by Aron Light in Portugal. Made in PRC

