

TECHNICAL INFORMATIONS

RÉGUA T5 PRO 110LM/W

22W 150CM IP20

Réguas de LED T5 PRO 110Lm.W com uma baixa altura de construção e possibilidade de criar linhas de luz contínuas com conexão simples.

LED T5 Battens with a low construction height and the possibility of creating continuous light lines with simple connection.

Regletas de LED T5 con una baja altura de construcción y posibilidad de crear líneas de luz continuas con conexión simples.




ILAR-00889

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Led Type	-	Dimensions (L x W x H)	1433x35mm	Total Luminous Flux	2420lm
Body Material	PVC	Weight	-	Luminous Efficacy	110lm / W
Fixings	-	Volume	-	Beam Angle	300°
Housing Colour	White	Model	Single	Colour Temperature	4000K
Nominal Lifetime (EOL end of life)	25000H	PC / BOX	30 pcs/carton	Colour Rendering Index	>80
Dimmable	-			Colour Consistency	-
Base	-				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	22W	Energy Label	A+	CE	YES
Nominal Voltage	100-240V	Energy Consumption KWH/1000H	-	ROHS	YES
Operating Frequency	50Hz	Type of Protection	IP20	ENEC	-
Power Factor	>0.95	Protecion Class IK (shock resistance)	-	Warranty	2 YEARS
Starting Time 100% ON	0.0001s				
ON/OFF Cycles	100000H				
Operating Temperature	-				

SIZE



Designed by Aron Light in Portugal. Made in PRC

