



TECHNICAL INFORMATIONS

TUBO T5 LED

18W 4000K

Tubo de vidro Standard com conexão nos dois topos e 110 LM / W.

Standard glass tube with double side connection and 110 LM / W.

Tubo Standard de Cristal Glass, con conexión en los dos lados y 110 LM / W.

ILAR-00488



REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Base	G5	Tube Diameter	16mm	Total Luminous Flux	1980lm
Body Type	GLASS	Length	1149mm	Luminous Efficacy	110lm/W
Conection to Power	Dual Ended - 2P	Weight	150g	Beam Angle	320°
Nominal Lifetime (EOL end of life)	25000H	Packaging Unit	50pcs	Colour Temperature	4000K
Switching Cycle (times)	50000X	Dimensions (L x W x H)	120x22.5x13.5cm	Colour Rendering Index	>80
Dimmable	NO	Gross Weight	9kg		
Mercury Free	YES	Volume	0.0365		
Microwave Sensor	NO				
Plastic Proteccion	NO				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Rated Voltage	18W	Energy Label	A+	CE Marking	YES
Nominal Wattage	18W	Energy Consumption KWH/1000H	18kWh	ROHS	YES
Nominal Current	0.164A	Type of Protection	IP20		
Nominal Voltage	180-265V				
Operating Frequency	50/60Hz				
Type of Current	AC				
Power Factor	0.5				
Starting Time	0.05s				
Warm - Up Time (60%)	0.5s				
Operating Temperature	-20° C to + 45° C				

SIZE



Designed by Aron Light in Portugal Made in PRC

