



## TECHNICAL INFORMATIONS

# TUBO T8 LED STANDARD

## 22W 6500K LN

Tubo de vidro Standard com conexão em um só topo e 110 LM / W.

Standard glass tube with single side connection and 110 LM / W.

Tubo Standard de Cristal Glass, con conexión por un lados y 110 LM / W.


**ILAR-00297**



REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Base	G13	Tube Diameter	26mm	Total Luminous Flux	2420lm
Body Type	GLASS	Length	1500mm	Luminous Efficacy	110lm/W
Conection to Power	Single Ended - 1P	Weight	300g	Beam Angle	320°
Nominal Lifetime (EOL end of life)	25000H	Packaging Unit	25PCS	Colour Temperature	6500K
Switching Cycle (times)	50000X	Dimensions (L x W x H)	158x20x20cm	Colour Rendering Index	>80
Dimmable	NO	Gross Weight	12.5kg		
Mercury Free	YES	Volume	0.0616		
Microwave Sensor	NO				
Plastic Proteccion	NO				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Rated Voltage	22W	Energy Label	A+	CE Marking	YES
Nominal Wattage	22W	Energy Consumption KWH/1000H	22kWh	ROHS	YES
Nominal Current	0.1954A	Type of Protection	IP20		
Nominal Voltage	180-265V				
Operating Frequency	50/60Hz				
Type of Current	AC				
Power Factor	0.5				
Starting Time	0.05s				
Warm - Up Time (60%)	0.5s				
Operating Temperature	-20° C to + 45° C				

### SIZE



Designed by Aron Light in Portugal. Made in PRC

