



## TECHNICAL INFORMATIONS

# TUBO T8 LED TECNIC 130LM/W

## 18W 3000K LN

Tubo de vidro Standard com conexão em um só topo e 130 LM / W, P.F. >0.9.

Standard glass tube with single side connection and 130 LM / W, P.F. >0.9.

Tubo Standard de Cristal Glass, con conexión por un lados y 130 LM / W, P.F. >0.9.



### ILAR-00500

#### REFERENCE

Base	G13
Body Type	GLASS
Conection to Power	Single Ended - 1P
Nominal Lifetime (EOL end of life)	25000H
Switching Cycle (times)	50000X
Dimmable	NO
Mercury Free	YES
Microwave Sensor	NO
Plastic Proteccion	NO

#### DIMENSION & WEIGHT

Tube Diameter	26mm
Length	1200mm
Weight	220g
Packaging Unit	25PCS
Dimensions (L x W x H)	124x20x20cm
Gross Weight	10.5kg
Volume	0.0496

#### PHOTOMETRICAL DATA

Total Luminous Flux	2340lm
Luminous Efficacy	130lm/W
Beam Angle	320°
Colour Temperature	3000K
Colour Rendering Index	>80

#### ELECTRICAL AND OPERATING DATA

Rated Voltage	18W
Nominal Wattage	18W
Nominal Current	0.09A
Nominal Voltage	85-265V
Operating Frequency	50/60Hz
Type of Current	AC
Power Factor	0.9
Starting Time	0.05s
Warm - Up Time (60%)	0.5s
Operating Temperature	-20° C to + 45° C


#### ENERGY LABEL & STANDARS

Energy Label	A+
Energy Consumption KWH/1000H	18kWh
Type of Protection	IP20

#### CERTIFICATIONS

CE Marking	YES
ROHS	YES

#### SIZE



Designed by Aron Light in Portugal. Made in PRC

