



TECHNICAL INFORMATIONS

TUBO T8 LED TECNIC 130LM/W

22W 4500K LN

Tubo de vidro Standard com conexão em um só topo e 130 LM / W, P.F. >0.9.

Standard glass tube with single side connection and 130 LM / W, P.F. >0.9.

Tubo Standard de Cristal Glass, con conexión por un lados y 130 LM / W, P.F. >0.9.




ILAR-00504

| REFERENCE | | DIMENSION & WEIGHT | | PHOTOMETRICAL DATA | |
|------------------------------------|-------------------|------------------------|-------------|------------------------|---------|
| Base | G13 | Tube Diameter | 26mm | Total Luminous Flux | 2860lm |
| Body Type | GLASS | Length | 1500mm | Luminous Efficacy | 130lm/W |
| Conection to Power | Single Ended - 1P | Weight | 300g | Beam Angle | 320° |
| Nominal Lifetime (EOL end of life) | 25000H | Packaging Unit | 25PCS | Colour Temperature | 4500K |
| Switching Cycle (times) | 50000X | Dimensions (L x W x H) | 154x20x20cm | Colour Rendering Index | >80 |
| Dimmable | NO | Gross Weight | 12.5kg | | |
| Mercury Free | YES | Volume | 0.0616 | | |
| Microwave Sensor | NO | | | | |
| Plastic Proteccion | NO | | | | |

| ELECTRICAL AND OPERATING DATA | | ENERGY LABEL & STANDARS | | CERTIFICATIONS | |
|-------------------------------|-------------------|------------------------------|-------|----------------|-----|
| Rated Voltage | 22W | Energy Label | A+ | CE Marking | YES |
| Nominal Wattage | 22W | Energy Consumption KWH/1000H | 22kWh | ROHS | YES |
| Nominal Current | 0.11A | Type of Protection | IP20 | | |
| Nominal Voltage | 85-265V | | | | |
| Operating Frequency | 50/60Hz | | | | |
| Type of Current | AC | | | | |
| Power Factor | 0.9 | | | | |
| Starting Time | 0.05s | | | | |
| Warm - Up Time (60%) | 0.5s | | | | |
| Operating Temperature | -20° C to + 45° C | | | | |

SIZE



Designed by Aron Light in Portugal. Made in PRC

