



## TECHNICAL INFORMATIONS

# TUBO T8 LED HIGH LUMEN

## 14W 6500K LN

Tubo de vidro high lumen com conexão em um só topo e 180 LM / W.

High lumen glass tube with single side connection and 180 LM / W.

Tubo high lumen de Cristal Glass, con conexión por un lados y 180 LM / W.

**ILAR-00865**



REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Base	G13	Tube Diameter	26mm	Total Luminous Flux	2520lm
Body Type	GLASS	Length	1200mm	Luminous Efficacy	180lm/W
Conection to Power	Single Ended - 1P	Weight	220g	Beam Angle	320°
Nominal Lifetime (EOL end of life)	50000H	Packaging Unit	25pcs	Colour Temperature	6500K
Switching Cycle (times)	50000X	Dimensions (L x W x H)	128x20x20cm	Colour Rendering Index	>80
Dimmable	NO	Gross Weight	10.5kg	Power Factor	>0.9
Mercury Free	YES	Volume	0.0496		
Microwave Sensor	NO				
Plastic Protecccion	NO				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Rated Voltage	14W	Energy Label	A+	CE Marking	YES
Nominal Wattage	14W	Energy Consumption KWH/1000H	14kWh	ROHS	YES
Nominal Current	0.134A	Type of Protection	IP20		
Nominal Voltage	85-265V				
Operating Frequency	50/60Hz				
Type of Current	AC				
Starting Time	0.05s				
Warm - Up Time (60%)	0.5s				
Operating Temperature	-20° C to + 45° C				

### SIZE



Designed by Aronlight in Portugal. Made in PRC

