



TECHNICAL INFORMATIONS

TUBO T8 LED STANDARD

12W 4000K LN

Tubo de vidro Standard com conexão em um só topo e 110 LM / W.

Standard glass tube with single side connection and 110 LM / W.

Tubo Standard de Cristal Glass, con conexión por un lados y 110 LM / W.


ILAR-02025



| REFERENCE | | DIMENSION & WEIGHT | | PHOTOMETRICAL DATA | |
|------------------------------------|-------------------|--------------------|-------|------------------------|---------|
| Base | G13 | Tube Diameter | 26mm | Total Luminous Flux | 1220lm |
| Body Type | GLASS | Length | 900mm | Luminous Efficacy | 110lm/W |
| Conection to Power | Single Ended - 1P | Weight | 120g | Beam Angle | 320° |
| Nominal Lifetime (EOL end of life) | 25000H | Packaging Unit | 25PCS | Colour Temperature | 4000K |
| Switching Cycle (times) | 50000X | | | Colour Rendering Index | >80 |
| Dimmable | NO | | | | |
| Mercury Free | YES | | | | |
| Microwave Sensor | NO | | | | |
| Plastic Proteccion | NO | | | | |

| ELECTRICAL AND OPERATING DATA | | ENERGY LABEL & STANDARS | | CERTIFICATIONS | |
|-------------------------------|-------------------|------------------------------|-------|----------------|-----|
| Rated Voltage | 12W | Energy Label | E | CE Marking | YES |
| Nominal Wattage | 12W | Energy Consumption KWH/1000H | 12kWh | ROHS | YES |
| Nominal Current | 0.078A | Type of Protection | IP20 | | |
| Nominal Voltage | 180-265V | | | | |
| Operating Frequency | 50/60Hz | | | | |
| Type of Current | AC | | | | |
| Power Factor | 0.5 | | | | |
| Starting Time | 0.05s | | | | |
| Warm - Up Time (60%) | 0.5s | | | | |
| Operating Temperature | -20° C to + 45° C | | | | |

SIZE



Designed by Aron Light in Portugal. Made in PRC

